



Part NO.	A	B	C	D	E	F	G	H	working stroke	Spring force (g)	针轴镀金	电流	寿命
BP13902	14.00	12.50	/	/	1.45	1.00	0.80	0.80	1.00	40g	5u''	2A	20000
BP02921	14.50	9.65	/	/	2.67	2.11	2.30	0.64	2.50	120g	20u''	2A	20000
BP06011	14.60	12.00	0.50	1.80	1.58	1.10	2.60	0.60	1.50	100g	20u''	3A	50000
BP17311	15.05	11.05	/	/	6.00	4.30	5.00	1.00	2.10	500g	10u''	2A	20000
BP11911	15.50	9.00	1.00	3.00	1.65	0.90	2.50	1.00	3.00	100g	3u''	1A	20000
BP06511	16.00	14.00	0.40	1.80	1.50	1.00	1.50	0.60	1.50	130g	3u''	1A	10000
BP22301	16.00	9.50	1.00	9.00	5.00	4.00	3.00	2.00	4.00	50g	/	1A	10000
BP17611	16.12	13.30	/	/	4.00	3.00	3.30	3.30	1.30	100g	100u''	1A	25000
BP26811	16.50	10.00	/	/	2.40	1.50	2.50	1.00	4.00	100g	10u''	2.5A	20000
BP08011	17.10	11.00	/	/	3.00	2.50	1.60	1.00	1.00	220g	3u''	2.5A	20000
BP26311	20.00	18.30	0.40	1.80	1.50	1.00	1.75	0.50	1.00	40g	10u''	1A	50000
BP24611	22.75	13.75	0.75	10.00	8.00	6.00	1.25	2.00	6.00	500g	/	1A	10000
BP18401	29.00	23.00	0.50	3.50	3.00	2.00	2.50	1.50	2.00	100g	3u''	2A	20000
BP01111	42.40	34.80	/	/	6.00	3.50	7.60	3.50	5.50	200g	/	/	10000