



Part NO.	A	B	C	D	E	F	G	H	working stroke	Spring force(g)	针轴镀金	电流	寿命
BP26611	9.20	6.90	0.55	1.80	1.48	0.80	4.40	0.65	1.00	70g	15u''	1A	50000
BP12511	9.20	5.25	/	/	6.00	4.30	2.50	1.00	2.00	500g	20u''	3A	20000
BP17511	9.50	7.90	0.50	4.80	2.00	1.20	4.00	1.00	1.40	160g	/	1A	20000
BP19501	9.50	8.00	/	/	5.00	3.20	1.00	1.00	1.50	150g	5u''	3A	20000
BP18402	9.50	6.50	0.50	3.00	2.50	1.50	2.50	1.50	2.00	65g	3u''	2A	20000
BP19301	9.80	8.00	/	/	2.40	1.60	1.60	1.00	1.00	140g	5u''	5A	20000
BP08611	9.80	7.30	2.50	2.50	1.80	1.30	2.50	1.02	0.80	85g	30u''	4.5A	40000
BP10911	9.80	8.30	/	/	2.50	1.50	2.10	1.95	1.30	190g	10u''	5A	20000
BP16811	10.00	7.90	0.40	1.80	1.48	1.00	1.00	0.80	1.00	80g	20u''	3A	100000
BP24711	10.00	7.00	/	/	2.00	1.20	2.00	0.80	2.80	120g	4u''	1A	20000
BP22001	10.00	7.00	0.50	2.50	1.50	1.00	0.80	1.50	1.00	100g	5u''	2A	20000
BP09411	10.20	7.00	3.70	2.90	2.50	1.80	1.90	1.00	3.00	120g	10u''	1A	100000
BP08911	10.20	7.40	0.50	1.80	1.50	1.00	1.10	1.00	1.20	110g	10u''	1A	20000
BP09411	10.20	7.00	3.70	2.90	2.50	1.80	1.90	1.00	3.00	120g	10u''	1A	100000
BP25911	10.30	8.50	/	/	2.50	1.50	1.50	1.50	1.00	120g	5u''	2A	20000
BP15511	10.90	8.70	0.50	1.80	1.48	1.00	2.50	0.60	1.40	110g	10u''	1A	20000