



Part NO.	A	B	C	D	E	F	G	H	working stroke	Spring force (g)	针轴镀金	电流	寿命
BP27911	11.00	7.30	0.40	1.80	1.48	1.00	3.00	0.50	1.00	70g	5u''	3A	50000
BP07311	11.00	9.00	/	/	1.50	0.90	4.00	0.60	1.00	80g	1u''	1.5A	10000
BP16101	11.00	8.00	/	/	3.00	2.20	5.00	2.20	1.00	80g	3u''	1A	20000
BP17022	11.50	7.00	/	/	4.00	3.30	1.50	1.50	1.50	220g	100u''	/	20000
BP21201	11.60	10.95	0.50	2.80	2.30	R1.00	2.00	1.20	0.60	120g	10u''	1A	20000
BP20901	11.80	8.50	/	/	2.00	1.02	6.00	1.40	1.00	90g	20u''	3A	20000
BP19011	11.80	9.00	/	/	2.00	1.20	3.00	1.50	2.80	150g	3u''	1A	20000
BP18101	12.10	8.15	6.65	5.00	4.00	3.00	4.30	4.00	1.00	120g	20u''	8A	20000
BP14711	12.30	9.00	/	/	1.80	1.00	3.95	1.20	0.70	90g	20u''	3A	50000
BP24211	13.00	9.50	/	/	2.80	2.00	3.00	1.00	2.50	150g	20u''	2A	100000
BP27211	13.20	10.00	/	/	2.80	2.00	2.60	1.20	1.70	96g	20u''	1A	20000
BP02911	13.21	9.65	/	/	2.67	2.11	2.29	0.64	2.50	120g	3u''	2A	100000
BP02912	13.21	9.65	/	/	2.67	2.11	2.29	0.64	1.19	120g	20u''	2A	100000
BP12911	13.35	10.85	0.50	2.00	1.48	0.90	2.00	0.80	0.80	40g	10u''	2A	20000